



MS-A 5W-30 BY MOTUL

Gasoline and Diesel Engine Lubricant

100% Synthetic

TYPE OF USE

MS-A 5W-30 BY MOTUL is a high performance 100% synthetic lubricant endorsed by MUGEN. It is specially designed by MOTUL for Honda Road Cars.

Suitable for new generation engines (gasoline, diesel, LPG, turbocharged and direct injection).

PERFORMANCE

MS-A 5W-30 BY MOTUL is specially formulated with technology derived from Super GT and Super Formula motorsports, modified for Asian market in term of viscometric, and additive technology rebalanced for road-going engines.

It has been developed to provide the following protection:

- High HTHS for modern engine protection
- Excellent shear stability for extended protection and engine durability
- Protection from Low Speed Pre-Ignition (LSPI) to prevent premature hardware failure
- Outstanding detergent and dispersant properties and superior anti-sludge and anti-wear performance to keep engine clean

RECOMENDATIONS

Drain interval : according to manufacturers' recommendations and tuned to your own use.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 15°C (59°F)	ASTM D4052	0.849
Viscosity at 40°C (104°F)	ASTM D445	69.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	12.0 mm ² /s
Viscosity index	ASTM D2270	171
TBN	ASTM D2896	11.7 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site: www.motul.fr